


XE-SP Series

- 👍 For tiny object detection.
- 👍 Low cost, tiny and with built-in amplifier.
- 👍 Excellent stability with perfect anti interference: anti invert frequency, anti electric noise (high frequency florescent light), anti electromagnetic wave, anti sunlight..etc.
- 👍 With Light ON or Dark ON function.
- 👍 Versatile Detection distance.



Model number	Switching output	Sensing distance	Sensing method	Operating voltage
XE-SP2MNE1	NPN NO	290cm	Through-beam	DC 12~24V ripple ≤ 10%
XE-SP50MNE1		50cm		
XE-SP2MNE2	NPN NC	290cm		
XE-SP50MNE2		50cm		
XE-SP2MPE1	PNP NO	290cm		
XE-SP50MPE1		50cm		
XE-SP2MPE2	PNP NC	290cm		
XE-SP50MPE2		50cm		

Item	Specifications
Control output	NPN NO · NPN NC · PNP NO · PNP NC
Response time	< 5ms
Load current	< 100mA
Light source	Infraed LED
Operation indicator	Red LED
Circuits protection	Reversed polarity & Short circuit protection
Enclosure protection	IEC IP65
Ambient temperature & humidity range	Operating : -20 ~ 55°C / RH 35 ~85% (with no icing or condensation)
Ambient illumination	Lamplight < 3000 Lux / Sunlight < 10000 Lux

Connecting method	Pre-wired 2M Cable
Housing material	Case : ABS / Lens : Acrylic
Accessories	Mounting bracket · Screws